

# Pressure independent control valves

Datasheet **HERZ PICV**, Issue 0822

---

**General information**

This product is only intended for the purpose intended by the manufacturer. This also includes compliance with all associated product regulations. Changes or conversions are not permitted.

**Disposal**

Local and currently applicable legislation must be observed for disposal. The disposal of HERZ pressure independent control valves must not endanger the health or the environment.

**Materials note**

Pursuant to Article 33 of the REACH Regulation (EC No. 1907/2006), we are obliged to point out that the material lead is listed on the SVHC list and that all brass components manufactured in our products exceed 0.1% (w / w) lead (CAS: 7439-92-1 / EINECS: 231-100-4). Since lead is a component part of an alloy, actual exposure is not possible and therefore no additional information on safe use is necessary.


All specifications and statements within this document are according to information available at the time of printing and meant for informational purpose only. Herz Armaturen reserves the right to modify and change products as well as its technical specifications and/or its functioning according to technological progress and requirements. It is understood that all images of Herz products are symbolic representations and therefore may visually differ from the actual product. Colours may differ due to printing technology used. In case of any further questions don't hesitate to contact your closest HERZ Branch-office.

# HERZ Pressure independent control valves


Datasheet 1 **4006 xx**, 1 **4406 2x**; 1 **4206 xx**

**Dimensions in mm**


1 **4006 XX M SMART - MT**



1 **4206 XX M SMART - FT**



1 **4406 2X - MT**



Installation dimensions mm

| Models                         |            |                         | Order number | DN    | Thread, inch | L, mm | H1, mm | H2, mm | H*, mm | B1, mm | B2, mm | L1, mm | L2, mm |
|--------------------------------|------------|-------------------------|--------------|-------|--------------|-------|--------|--------|--------|--------|--------|--------|--------|
| MT - male thread, flat sealing | 4006 SMART | M - with test points    | 1 4006 30    | 15 LF | G ¾"         | 75    | 35     | 69     | 159    | 50     | 23     | 41     | 34     |
|                                |            |                         | 1 4006 39    | 15 MF | G ¾"         | 75    | 35     | 69     | 159    | 50     | 23     | 41     | 34     |
|                                |            |                         | 1 4006 51    | 15 SF | G ¾"         | 75    | 32     | 71     | 158    | 54,6   | 23,3   | 41     | 34     |
|                                |            |                         | 1 4006 71    | 15 HF | G ¾"         | 75    | 32     | 71     | 158    | 54,6   | 23,3   | 41     | 34     |
|                                |            | 1 4006 52               | 20 SF        | G 1"  | 75           | 32    | 71     | 158    | 55,6   | 23,2   | 41     | 34     |        |
|                                |            | 1 4006 72               | 20 HF        | G 1"  | 75           | 32    | 71     | 158    | 55,6   | 23,2   | 41     | 34     |        |
|                                |            | R - without test points | 1 4006 91    | 15 SF | G ¾"         | 75    | 32     | 71     | 158    | 30,6   | 23,3   | 41     | 34     |
|                                |            |                         | 1 4006 81    | 15 HF | G ¾"         | 75    | 32     | 71     | 158    | 30,6   | 23,3   | 41     | 34     |
|                                | 1 4006 92  |                         | 20 SF        | G 1"  | 75           | 32    | 71     | 158    | 31,6   | 23,2   | 41     | 34     |        |
|                                | 1 4006 82  |                         | 20 HF        | G 1"  | 75           | 32    | 71     | 158    | 31,6   | 23,2   | 41     | 34     |        |
|                                | 4406       | M - with test points    | 1 4406 23    | 25    | G 1 ¼"       | 75    | 76     | 170    | 218    | 61     | 134    | 133    | -      |
|                                |            |                         | 1 4406 24    | 32    | G 1 ¾"       | 100   | 93     | 188    | 236    | 69     | 145    | 138    | -      |
|                                |            |                         | 1 4406 25    | 40    | G 2"         | 110   | 93     | 194    | 242    | 77     | 161    | 143    | -      |
|                                |            |                         | 1 4406 26    | 50    | G 2 ½"       | 130   | 93     | 194    | 242    | 77     | 163    | 153    | -      |
| FT - female thread             | 4206 SMART | M - with test points    | 1 4206 20    | 15 LF | Rp ½"        | 75    | 35     | 67     | 157    | 50     | 23     | 41     | 34     |
|                                |            |                         | 1 4206 29    | 15 MF | Rp ½"        | 75    | 35     | 67     | 157    | 50     | 23     | 41     | 34     |
|                                |            |                         | 1 4206 01    | 15 SF | Rp ½"        | 75    | 32     | 70,9   | 158    | 55,2   | 23,2   | 41     | 34     |
|                                |            |                         | 1 4206 71    | 15 HF | Rp ½"        | 75    | 32     | 70,9   | 158    | 55,2   | 23,2   | 41     | 34     |
|                                |            |                         | 1 4206 02    | 20 SF | Rp ¾"        | 75    | 32     | 70,9   | 158    | 55,6   | 23,3   | 41     | 34     |
|                                |            |                         | 1 4206 72    | 20 HF | Rp ¾"        | 75    | 32     | 70,9   | 158    | 55,6   | 23,3   | 41     | 34     |
|                                |            | R - without test points | 1 4206 60    | 15 LF | Rp ½"        | 75    | 35     | 67     | 157    | 26     | 23     | 41     | 34     |
|                                |            |                         | 1 4206 69    | 15 MF | Rp ½"        | 75    | 35     | 67     | 157    | 26     | 23     | 41     | 34     |
|                                | 1 4206 91  |                         | 15 SF        | Rp ½" | 75           | 32    | 70,9   | 158    | 31,2   | 23,2   | 41     | 34     |        |
|                                | 1 4206 81  |                         | 15 HF        | Rp ½" | 75           | 32    | 70,9   | 158    | 31,2   | 23,2   | 41     | 34     |        |
|                                | 1 4206 92  |                         | 20 SF        | Rp ¾" | 75           | 32    | 70,9   | 158    | 31,6   | 23,3   | 41     | 34     |        |
|                                | 1 4206 82  |                         | 20 HF        | Rp ¾" | 75           | 32    | 70,9   | 158    | 31,6   | 23,3   | 41     | 34     |        |

\* with 1 7990 3X actuator

 Technical Data

|                                  |                  | 4006 / 4206 SMART   |      |      |      |        |       | 4406 |      |      |        |
|----------------------------------|------------------|---|------|------|------|--------|-------|------|------|------|--------|
|                                  |                  | 15LF  | 15MF | 15SF | 15HF | DN20SF | 20HF  | DN25 | DN32 | DN40 | DN50   |
| Max flow l/h                     | 6,5 mm actuator* | 120   | 190  | 800  | 1200 | 1200   | 2000  | 3500 | 6000 | 7500 | 12500  |
|                                  | 5 mm actuator*   |   |      |      |      |        |       | 2650 | 4500 | 5650 | 9400   |
| Flow setting range               |                  | 20 - 100%   |      |      |      |        |       |      |      |      |        |
| Diff. pressure across valve, kPa | $\Delta p_{min}$ | 18  | 20   | 20   | 20   | 20     | 20-30 | 35   | 35   | 35   | 40     |
|                                  | $\Delta p_{max}$ | 400   | 400  | 600  | 600  | 600    | 600   | 600  | 600  | 600  | 600    |
| PN                               |                  | 25 bar  |      |      |      |        |       |      |      |      |        |
| Min. operating temperature       |                  | 2 °C (water); - 20 °C (non-freezing)  |      |      |      |        |       |      |      |      |        |
| Max. operating temperature       |                  | 130 °C  |      |      |      |        |       |      |      |      | 110 °C |
| Stroke                           |                  | 4 mm  |      |      |      |        | 6 mm  |      |      |      |        |
| Actuator connection              |                  | M 28 x 1,5  |      |      |      |        |       |      |      |      |        |
| Water quality                    |                  | Water purity in accordance with the ÖNORM H 5195 and VDI 2035 standards<br>Ethylene and propylene glycol can be mixed to a ratio of 25 - 50 vol. [%]. |      |      |      |        |       |      |      |      |        |

\* The integrated control unit together with the actuating drive is responsible for modular control. The max. flow with 6.5 drive is achieved with the 1 7990 32 actuating drive or with the 1 7708 4X geared motors. When using the 1 7990 31 and 1 7708 52/53 actuators with a 5 mm stroke, the maximum flow rate is reduced. The 4006 / 4206 SMART valves with a 4 mm stroke can be driven with all linear HERZ drives.


 Field of application

The Pressure Independent Balancing Control Valve (PIBCV) is used in all heating and cooling systems with circulation pumps. The valve automatically maintains flow to the required part of the system constant at the set rate by measuring and immediately adjusting to any variation in pressure.

**Materials**

| N  | Description    | Materials       |
|----|----------------|-----------------|
| 1  | Body           | DZR brass       |
| 2  | Membrane body  | brass           |
| 3  | Pin            | stainless steel |
| 4  | Membrane       | EPDM            |
| 5  | O-rings        | EPDM            |
| 6  | Spring         | stainless steel |
| 7  | capillary pipe | copper Cu-DHP   |
| 8  | Pin            | stainless steel |
| 9  | Spring         | stainless steel |
| 10 | Protective cap | plastic         |

The use of ethylene and propylene glycol in a mixture ratio of 25 - 50% by volume [%] is permitted. No hemp should be used for thread sealing because the ammonia contained in hemp can damage the brass. It is recommended to use sealing strip. EPDM seals are swollen by mineral oils or lubricants containing mineral oil and thus lead to failure of the EPDM seals. For frost and corrosion protection agents based on ethylene and propylene glycol can be found in the manufacturer's documentation.




The valve settings directly affect the volumetric flow through the valve. It is thus possible to set the maximum flow rate based on the flow chart when the valve is fitted. This allows for the balancing of heating circuits, cooling water systems, ceiling cooling and heating panels, air heaters, etc. without any need to first assess the pressure variations in the system.

**System flushing**

If it is necessary to flush the system in the direction opposite to the direction of valve's operation, it is important to take into account the maximum allowed differential pressure on the valve for backflushing, equal to 300 kPa. The volume flow during backflushing should be a maximum of three times the nominal flow rate.

**Installation**

The installation takes place in the return or in the supply, the installation position does not matter. The direction of flow is indicated in the direction of the arrow on the housing. It is recommended to install a shut-off valve before and after the combination valve. The combination valve is shut off with the HERZ setting tool (1 4006 02). The desired flow rate is set in % of the maximum flow rate. Shut off by turning to the right to the stop (display < 0% red area).



### ☑ Application field

It is assumed that a consumer needs a volume flow of 600 l/h. The setting value is searched for the HERZ combination valve SMART DN 15SF (1 4006 51/91, 1 4206 01/91). The maximum flow at valve DN 15SF is 800 l/h, that corresponds to the setting 100%:

$$\frac{600 \text{ l/h}}{800 \text{ l/h}} \times 100 \% = 75 \%$$

The 600 l/h is required thus presetting is 75%, which must be set on the valve. A control measurement is then to be carried out. Please note that a minimum differential pressure according to the data sheet must be available for correct operation on the valve.

The HERZ combi valve 4006 is operated with 2-point or continuously acting actuators. However, continuous control is always recommended. The reason for this is that constant and energy-saving control is essential for fast-working systems such as cooling systems or air heaters. Maximum energy savings can only be achieved with regulating valves.

With continuous control, the volume flow is controlled continuously with the slightest fluctuations between minimum and maximum flow. The continuous control also protects all other system-specific components, right down to the pump. The 2-point control is recommended for slow systems such as underfloor heating.

HERZ 4006 PICVs have several advantages over conventional series connection of volume flow controller and differential pressure controller, since the volume flow controller limits the flow depending on the differential pressure of the system, while the differential pressure is variable. If the amount of water is reduced when the room temperature is reached, the differential pressure increases. The resulting operating point is completely different from that of hydraulic balancing. This means that valves connected in series interfere with themselves.

The valve authority for the HERZ combination valve is ideally "1". A valve authority below 0.3 is an ON / OFF control. In order to ensure the efficiency of your system and proper operation, modular control with an authority greater than 0.5 should be aimed for. Since the HERZ valve 4006 compensates for the different differential pressures, the volume flow to the consumer is kept constant. An over or under supply of the individual consumers is therefore excluded.

Hydraulic balancing is always a relevant topic in building technology. The combination valves 4006, 4006 SMART and 4206, 4206 SMART enable the construction of a technical building system with reduced planning effort.

For systems with a large number of PICVs installed, the use of a differential pressure control valves 4002 is recommended to avoid noise problems, the occurrence of water hammer and an unstable system operation.

### ☑ Valve selection


Select the valve with the smallest dimension that guarantees the necessary nominal flow with an additional safety surcharge. The setting should be as open as possible.

The flow rate calculation is based on the following formula:

$$V = \frac{3600 \times Q}{c \times \rho \times \Delta T} \times 1000, [\text{l/h}]$$


V ... volume flow [l/h]  
 Q ... heat output [kW]  
 c ... specific heat capacity 4.19 [kJ/kgK]  
 ρ ... density of water [kg/m<sup>3</sup>]  
 ΔT ... temperature difference flow and return [K]

With the help of the kv diagram, the respective minimum differential pressure [kPa] can be determined depending on the flow [l/h] and the default setting [%].



**Application example**


Combi valves are used in fan coil heat supply systems. A combination valve is installed in the return of each fan coil and acts as regulating valve.



Schema of a four-pipes fan coil heat supply system (extract)

|   |  |
|---|--|
| 1 |  |
| 2 | <b>4115</b> shut-off valve STRÖMAX-A         |
| 3 | <b>4111</b> strainer                         |
| 4 | <b>4006</b> PICV SMART                       |
| 5 | <b>7990</b> actuating drive                  |
| 6 | <b>7793</b> electronic continuous controller |


PICVs in use with a hydraulic distributor




|    |  |
|----|--|
| 1  | <b>4406</b> PICV   |
| 2  | <b>7990</b> actuating drive                              |
| 3  | <b>4513</b> hydraulic switch                             |
| 4  | <b>4115</b> shut-off valve STRÖMAX-A                     |
| 5  | <b>4217</b> commissioning valve STRÖMAX-GM               |
| 6  | <b>4119</b> Boiler filling and draining valve THERMOFLEX |
| 7  | <b>4111</b> strainer                                     |
| 8  | circulation pump   |
| 9  | <b>7793</b> electronic continuous controller             |
| 10 | <b>7793</b> heating water temperature sensor             |
| 11 | Outside temperature sensor                               |

**Press fitting screw connection**


**T 70XX** Junction press fitting screw connection for composite pipes PE-RT for valve with male thread, flat-sealing

|  | Order number | Valve dimension | G        | Pipe     |
|---|--------------|-----------------|----------|----------|
|   | T 7016 41    | DN 15           | G 3/4"   | 16 x 2   |
|   | T 7020 41    | DN 15           | G 3/4"   | 20 x 2   |
|   | T 7016 42    | DN 20           | G 1"     | 16 x 2   |
|   | T 7020 42    | DN 20           | G 1"     | 20 x 2   |
|   | T 7026 42    | DN 20           | G 1"     | 26 x 3   |
|   | T 7026 43    | DN 25           | G 1 1/4" | 26 x 3   |
|   | T 7032 43    | DN 25           | G 1 1/4" | 32 x 3   |
|   | T 7040 43    | DN 25           | G 1 1/4" | 40 x 3,5 |
|   | T 7040 45    | DN 40           | G 2"     | 40 x 3,5 |
| T 7050 45   | DN 40        | G 2"            | 50 x 4   |          |


**T 70XX** Press fitting screw connection for composite pipes PE-RT for valve with female thread, flat-sealing

|  | Order number | Valve dimension | G      | Pipe   |
|--|--------------|-----------------|--------|--------|
|  | T 7016 61    | DN 15           | G 1/2" | 16 x 2 |
|  | T 7020 61    | DN 15           | G 3/4" | 20 x 2 |
|  | T 7016 62    | DN 20           | G 1"   | 16 x 2 |
|  | T 7020 62    | DN 20           | G 1"   | 20 x 2 |
| T 7026 62  | DN 20        | G 1"            | 26 x 3 |        |

**6220** Iron pipe connection flat seal with nut and seal

|  | Order number | Valve dimension | G        | R      | L, mm |
|---|--------------|-----------------|----------|--------|-------|
|   | 1 6220 21    | DN 15           | G 3/4"   | R 1/2" | 26,3  |
|   | 1 6220 12    | DN 20           | G 1"     | R 3/4" | 31,4  |
|   | 1 6220 63    | DN 25           | G 1 1/4" | R 1"   | 35,3  |
| 1 6220 65   | DN 32        | G 1 3/4"        | R 1 1/2" | 49     |       |

**6236** Solder connection

|  | Order number | Valve dimension | G        | Ø D, mm | L, mm |
|---|--------------|-----------------|----------|---------|-------|
|   | 1 6236 01    | DN 15           | G 3/4"   | Ø 12    | 14    |
|   | 1 6236 11    | DN 15           | G 3/4"   | Ø 15    | 17    |
|   | 1 6236 21    | DN 15           | G 3/4"   | Ø 18    | 19    |
|   | 1 6236 02    | DN 20           | G 1"     | Ø 15    | 18    |
|   | 1 6236 12    | DN 20           | G 1"     | Ø 18    | 19    |
|   | 1 6236 22    | DN 20           | G 1"     | Ø 22    | 23    |
|   | 1 6236 63    | DN 25           | G 1 1/4" | Ø 28    | 24    |
|   | 1 6236 65    | DN 32           | G 1 3/4" | Ø 42    | 31    |
| 1 6240 74   | DN 40        | G 2"            | Ø 35     | 27      |       |

**6240** Welding connection flat seal






|  | Order number     | Valve dimension | G      | Ø D, mm | L, mm |
|--|------------------|-----------------|--------|---------|-------|
|  | 1 <b>6240</b> 01 | DN 15           | G ¾"   | Ø 21,3  | 45    |
|  | 1 <b>6240</b> 02 | DN 20           | G 1"   | Ø 26,8  | 45    |
|  | 1 <b>6240</b> 63 | DN 25           | G 1 ¼" | Ø 33,7  | 51    |
|  | 1 <b>6240</b> 65 | DN 32           | G 1 ¾" | Ø 47,5  | 57    |

**Accessories**

| Order number     | Description   | Image |
|------------------|---|-------|
| 1 <b>7990</b> 32 | <b>HERZ actuating drive for continuous control, NC</b><br>M 28 x 1.5, 0..10 V, 6.5 mm stroke,<br>adapter M 28 x 1.5 colour blue integrated,<br>male connector, cable loose, without limit switch.<br>Closing force 125 N, 1.2 watt<br>with valve stroke detection.  |       |
| 1 <b>7990</b> 31 | <b>HERZ actuating drive for continuous control, NC</b><br>M 28 x 1.5, 0..10 V, 5 mm stroke,<br>adapter M 28 x 1.5 colour blue integrated,<br>male connector, cable loose, without limit switch.<br>Closing force 100 N, 1.2 watt.   |       |
| 1 <b>7708</b> 53 | <b>HERZ actuating drive for 2-point control for floor heating circuit distributors and valves, NC, 230 V/AC,</b> M 28 x 1.5,<br>2-point, also suitable for pulse-pause operation, 5 mm stroke,<br>adapter M 28 x 1.5 colour red integrated, cable fixed, without<br>limit switch. Closing force 100 N.<br>Power consumption 1 watt. |       |
| 1 <b>7708</b> 52 | <b>HERZ actuating drive for 2-point control for floor heating circuit distributors and valves, NC, 24 V/AC,</b><br>M 28 x 1.5, 2-point, also suitable for pulse-pause operation,<br>5 mm stroke, adapter M 28 x 1.5 colour red integrated, cable<br>fixed, without limit switch. Closing force 100 N.<br>Power consumption 1 watt   |       |
| 1 <b>7708</b> 40 | <b>HERZ geared motor 3-point, 24V/AC/DC</b><br>Adapter M 28 x 1.5 colour red integrated, 24 V,<br>stroke distance max. 8.5 mm, max. actuation force 200 N.  |       |
| 1 <b>7708</b> 41 | <b>HERZ geared motor 3-point, 230V/AC</b><br>Adapter M 28 x 1.5 colour red integrated, 230 V,<br>stroke distance max. 8.5 mm, max. actuation force 200 N.   |       |
| 1 <b>7708</b> 42 | <b>HERZ geared motor DDC 0-10 V</b><br>Adapter M 28 x 1.5 colour red integrated, 24 V,<br>stroke distance max. 8.5 mm, max. actuation force 200 N.<br>Operating voltage 24V/AC/DC.  |       |
| 1 <b>7708</b> 46 | <b>HERZ geared motor DDC 0-10 V</b><br>Adapter M 28 x 1.5 colour red integrated, 24 V, stroke distance<br>max. 8.5 mm, max. actuation force 200 N. With valve port<br>detection and feedback channel.<br>Operating voltage 24V/AC/DC.   |       |



Accessories and spare parts


| Order number | Dim. | Description  | Model   |
|--------------|------|--|---|
| 1 0284 05    | 1/8" | Quick test point for combi valve - pressure-independent control valve SMART, brass version, blue cap (return) for pressure transducer  |    |
| 1 0284 01    | 1/4" | Quick test point for combi valve - pressure-independent control valve, brass version, blue cap (return) for pressure transducer  |   |
| 1 0284 06    | 1/8" | Quick test point for combi valve - pressure-independent control valve SMART, brass version, red cap (supply) for pressure transducer   |    |
| 1 0284 02    | 1/4" | Quick test point for combi valve - pressure-independent control valve, brass version, red cap (supply) for pressure transducer   |   |
| 1 0284 11    | 1/4" | Quick test point for combi valve - pressure-independent control valve. brass version, blue cap (return) for pressure transducer, extended design for valves with an insulation thickness up to 40 mm |    |
| 1 0284 12    | 1/4" | Quick test point for combi valve - pressure-independent control valve. brass version, red cap (supply) for pressure transducer, extended design for valves with an insulation thickness up to 40 mm  |   |
| 1 4006 02    |      | Pre-setting key HERZ Combi valve pressure-independent control valve for 4006/4206  |  |

**Pressetting**

The respective setting of the control unit is clearly shown in percentages. The valve is preset with the HERZ setting key (1 4006 02). The desired flow is set in% of the maximum flow. To shut off, turn to the right to <0% (red area).

$$VE [\%] = (\text{Desired flow} / \text{maximum flow}) * 100$$


open = anticlockwise



1 4006 02



close = clockwise



How to perform a flow measurement:


- Connect the measuring computer to the measuring nipple
- Enter the dimensions, valve type and setting -> display flow

**Warning notices**


The valves must be installed for the correct application using clean fittings. A HERZ strainer (4111) should be fitted to prevent impurities

**Test points**

Two test points are fitted on the same side of the valve and factory sealed. Thanks to this arrangement they are easily accessible and measurement devices can be quickly fitted, no matter in what position the valve has been installed.







|  |                    |
|--|--------------------|
| HERZ - Standard diagram  | HERZ PICV SMART    |
| 1 4206 71, 1 4006 71, 1 4206 81, 1 4006 81<br>1 4206 02, 1 4006 52, 1 4206 92, 1 4006 92 | DN 15 HF, DN 20 SF |

